



Stålrør Sensimir
Forzinket

Steel duct Sensimir
Galvanized

Ø udv. Ext. dia.	Længde Length	Materialetykkelse mm Material thickness mm
050	3 m	1,25
063	3 m	1,25
076	3 m	1,50
102	3 m	1,50
108	3 m	1,50
127	3 m	1,50
152	3 m	1,50



Bøjning
El-forzinket

Bend
Zinc-plated

Ø udv. Ext. dia.	Bøjning Bend	Materialetykkelse mm Material thickness mm	Radius
050	45°	1,50	2,5
063	45°	1,50	1,5
076	45°	1,50	2,2
102	45°	2,00	1,5
108	45°	2,00	1,5
127	45°	2,00	1,3
152	45°	2,00	1,5

Ø udv. Ext. dia.	Bøjning Bend	Materialetykkelse mm Material thickness mm	Radius
050	90°	1,50	2,5
063	90°	1,50	1,5
076	90°	1,50	2,2
102	90°	2,00	1,5
108	90°	2,00	1,5
127	90°	2,00	1,3
152	90°	2,00	1,5



Bukserør 45°
El-forzinket

Trouser Piece 45°
Zinc-plated

Ø udv. A Ext. dia. A	Ø udv. B Ext. dia. B
050	050
063	063
076	076
102	102
108	108
127	127
152	152

**Grenør 45°**

El-forzinket

Branch piece 45°

Zinc-plated

Ø udv. A,B Ext. dia. A,B	Ø udv. A,B Ext. dia. A,B	Ø udv. A,B Ext. dia. A,B
050-050	102-102	127-127
063-050	108-050	152-063
063-063	108-063	152-076
076-050	108-076	152-102
076-063	108-108	152-108
076-076	127-063	152-127
102-050	127-076	152-152
102-063	127-102	
102-076	127-108	

**Reduktion**

El-forzinket

Taper

Zinc-plated

Ø udv. Ext. dia.	Ø udv. Ext. dia.	Ø udv. Ext. dia.
050-038	102-076	127-102
063-050	108-063	127-108
076-050	108-076	152-102
076-063	108-102	152-108
102-063	127-076	152-127

**Endebund**

El-forzinket

End cover

Zinc-plated

Diameter	Diameter
050	108
063	127
076	152
102	

**Rørkobling**

Galvaniseret med elektrisk ledende EPDM-gummi-indlæg

Duct coupling

galvanized with conductive EPDM rubber

Diameter	Diameter
050	108
063	127
076	152
102	